Data sheet



Motion detector

IS 3360

DALI - surface-mounted installation, round EAN 4007841033507



Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

Technical specifications

| Туре | Motion detectors |
|---|---|
| Dimensions (Ø x H) | 126 x 65 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| Sensor Technology | passive infrared |
| Application, place | outdoors, Indoors |
| Application, place, room | sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room |
| Type of installation | Surface wiring |
| Switching zones | 1416 switching zones |
| Electronic scalability | No |
| Mechanical scalability | No |
| Mounting height | 2,50 – 4,00 m |
| Optimum mounting height | 2,8 m |
| Detection angle | 360 ° |
| Angle of aperture | 180 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |
| Reach, radial | Ø 10 m (79 m²) |
| | |

Data sheet



Motion detector

IS 3360

DALI - surface-mounted installation, round EAN 4007841033507

Technical specifications

| Reach, tangential | Ø 40 m (1257 m²) |
|--|--|
| Reach, presence | Ø 3 m (7 m²) |
| Twilight setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Time setting | 5 sec – 15 min |
| Control output, DALI | Broadcast 1x30 electronic ballasts |
| Constant-lighting control | Yes |
| Basic light level function | Yes |
| Basic light level function in per cent | 10 – 50 % |
| Basic light level function time | 1-30 min, all night |
| Basic light level function percentage, from | 10 % |
| Basic light level function percentage, up to | 50 % |
| With remote control | No |
| Interconnection | Yes |
| IP rating | IP54 |
| Material | Plastic |
| Ambient temperature | -20 – 50 °C |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |
| Version | DALI - surface-mounted installation, round |
| PU1, EAN | 4007841033507 |

Data sheet



Motion detector

IS 3360

DALI - surface-mounted installation, round EAN 4007841033507

Mood image

