

Motion detector

SensIQ S

EVO Anthracite

EAN 4007841056650



Function description

The evolution of perfection. The sensIQ S is just as perfect as its larger role model. For indoors and outdoors, ideal for building entrances, loading bays, for mounting heights of up to 5 m, quadruple sensor system for optimum surveillance over 3 x 100° angle of coverage, 20 m reach (tangential), reach setting to the accuracy of a metre in 3 independent directions. Including remote control and corner wall mount.

Technical specifications

Type	Motion detectors
Type of accessory	Corner adapter
Dimensions (L x W x H)	114 x 74 x 128 mm
Mains power supply	100 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Installation site	wall, corner
Type of installation	Surface wiring
Switching zones	1360 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2,5 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)

Data sheet

Motion detector

SensIQ S

EVO Anthracite

EAN 4007841056650

Technical specifications

Reach, radial	r = 4 m (42 m ²)
Reach, tangential	r = 20 m (1047 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Switching output 1, resistive	2000 W
Constant-lighting control	No
Basic light level function	No
With remote control	Yes
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	Anthracite
IDs, certificates	VDE
Manufacturer's Warranty	5 years
Version	Anthracite
PU1, EAN	4007841056650

Mood image

