

Presence detector

IR Quattro

DALI

EAN 4007841002749



Function description

Squaring the circle. Infrared presence detector Presence Control PRO IR Quattro DALI for indoors, ideal for small offices, store, service and utility rooms, washrooms and WCs, installation height up to 8 m, with digital DALI interface for controlling 2 lighting channels, 1760 switching zones for excellent detection quality, square presence detection zone covering 16 m², mechanically scalable.

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	120 x 120 x 76 mm
Mains power supply	230 V, 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	One-person office, conference room, side room
Type of installation	Concealed wiring
Switching zones	1760 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,50 – 8,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, radial	5 x 5 m (25 m ²)
Reach, tangential	7 x 7 m (49 m ²)
Reach, presence	4 x 4 m (16 m ²)

Presence detector

IR Quattro

DALI

EAN 4007841002749

Technical specifications

Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	30 sec – 30 min
Control output, DALI	Broadcast 2x12 electronic ballasts
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function in per cent	10 – 60 %
Basic light level function time	1-60 min, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	60 %
Functions	Normal / test mode, Semi-/fully automatic, Pushbutton / switch mode, Manual ON / ON-OFF
With remote control	No
Interconnection	Yes
Type of interconnection	Master/slave
IP rating	IP20
Material	Plastic
Ambient temperature	-25 – 55 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	DALI
PU1, EAN	4007841002749

Data sheet



Presence detector

IR Quattro

DALI

EAN 4007841002749

Mood image

