

Anthracite EAN 4007841 052966 Article number 052966







Function description

Light for free. The solar light in anthracite illuminates house number without cables or costs – with nothing but energy from the sun. At dusk, light come ON automatically. In this version too, the patented intelligent microprocessor control system and the powerful lithium-iron-phosphate rechargeable batteries provide ensure reliable illumination. 365 days of the year. With night-light function, soft light start and evening light (4 h).

Technical specifications

Dimensions (L x W x H)	91 x 242 x 38 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	Anthracite
PU1, EAN	4007841052966
Application, place	Outdoors
Application, room	outdoors, front door, courtyard & driveway
Colour	Anthracite
Installation site	wall
Impact resistance	IK03
IP-rating	IP44
Protection class	III
Ambient temperature	from -20 up to 40 °C
Housing material	Aluminium

Photo-cell controller	Yes
Measured luminos flux (360°)	7 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
	Passive Thermo Control
LED cooling system	Passive Thermo Control
Soft light start	Yes
Soft light start	Yes
Soft light start Functions	Yes Light sensor
Soft light start Functions Twilight setting	Yes Light sensor 2 lx
Soft light start Functions Twilight setting Basic light level function	Yes Light sensor 2 lx Yes
Soft light start Functions Twilight setting Basic light level function Basic light level function time	Yes Light sensor 2 lx Yes all night

Page 1 from 2

05.2025



Anthracite EAN 4007841 052966 Article number 052966



Technical specifications

Cover material	Plastic, structured	Akku-Funktion	ab - 20	
Power supply, detail	Solar supply, no mains power required, Lithium-iron-phosphate	Product category	Solar light	
	rechargeable battery 2000 mAh			
Mounting height max.	2,50 m			

Dimension Drawing

