
Motion detector

**IS 1** black EAN 4007841 600419 Article number 600419







#### **Function description**

Targeted detection and attractive price. Infrared motion detector IS 1, for indoors and out, ideal for targeted coverage of small areas, 120° angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor turns through 30° and tilts through 180° for exact adjustment of the detection zone.

### **Technical specifications**

Dimensions (L x W x H)	120 x 80 x 50 mm	LED lamps > 2 W < 8 W	125 W
Manufacturer's Warranty	3 years	LED lamps > 8 W	250 W
Settings via	Potentiometers	Capacitive load in µF	88 μF
With remote control	No	Technology, sensors	passive infrared, Light sensor
Version	black	Mounting height	1,80 – 3,00 m
PU1, EAN	4007841600419	Mounting height max.	3,00 m
Туре	Motion detectors	Optimum mounting height	2 m
Application, place	Indoors, Outdoors	Detection angle	120 °
Application, room	outdoors, front door, all round the	Angle of aperture	40 °
	building, terrace / balcony, courtyard & driveway	Sneak-by guard	No
Colour	black	Capability of masking out individual segments	Yes
Colour, RAL	9005	Electronic scalability	Νο
Includes corner wall mount	No	Mechanical scalability	No
Installation site	wall, ceiling	Reach. radial	$r = 3 m (9 m^2)$
Installation	Surface wiring, Wall, Ceiling	Reach, tangential	$r = 10 \text{ m} (105 \text{ m}^2)$
IP-rating	IP54	Switching zones	260 switching zones
Protection class	II		200 Switching 20105

05.2025 Page 1 from 3

# IS 1 black

EAN 4007841 600419 Article number 600419



# **Technical specifications**


Ambient temperature	from -20 up to 50 °C	
Material	Plastic	
Mains power supply	230 – 240 V / 50 Hz	
Switching output 1, resistive	500 W	
Fluorescent lamps, electronic ballast250 W		
Fluorescent lamps, uncorrected	500 VA	
Fluorescent lamps, series-corrected	I 500 VA	
Fluorescent lamps, parallel- corrected	500 VA	
Switching output 1, low-voltage halogen lamps	500 VA	
LED lamps < 2 W	100 W	

Twilight setting	2 – 2000 lx	
Time setting	8 s – 35 Min.	
Basic light level function	No	
Main light adjustable	No	
Twilight setting TEACH	No	
Constant-lighting control	No	
Interconnection	Yes	
Type of interconnection	Master/master	
Interconnection via	Cable	
Product category	Motion detector	

**IS 1** black EAN 4007841 600419 Article number 600419




# **Detection Zone**




Possible mounting height: 1,80 m – 3,00 m Orange: radial Black: tangential


### Light without neutral conductor




# Connection using two-circuit switch for manual and automatic operation



**Dimension Drawing** 



## Light with neutral conductor



Circuit diagram Connection via a changeover switch for continuous and automatic operation

