


Photo-cell controller

NightMatic 2000

black

EAN 4007841 550318

Article number 550318



Twilight switch

1000 W

1000 W max.
(LED-ready)



IP54



2 - 30 lux



energy saving

3 years

manufacturer's
warranty
steinel.de/garantie



CE



TÜV Nord
Baumuster
checked

Function description

Automatic illumination. Photo-electric lighting controller NightMatic 2000, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn.

Technical specifications

Type	Photo-cell controller
Dimensions (L x W x H)	37 x 74 x 99 mm
Mains power supply	230 – 240 V / 50 Hz
Power consumption	0,8 W
Sensor Technology	Light sensor
Application, place	Outdoors
Installation site	wall
Installation	Surface wiring
Twilight setting TEACH	Yes
Twilight setting	2 – 30 lx
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	4 pcs.
Fluorescent lamps, uncorrected	500 VA
Capacitive load in µF	88 µF

Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
Interconnection	Yes
Type of interconnection	Master/master
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841550318

Photo-cell controller

NightMatic 2000

black

EAN 4007841 550318

Article number 550318



Dimension Drawing

