

# HG 2120 E carwrapper-edition

EAN 4007841 008024



CE



VDE

## Function description

Experts in vehicle wrapping. Electronically controlled hot air tool HG 2120 E with 7.5 m cable. 2200 W, infinitely adjustable temperature from 80 – 630 °C, airflow rate adjustable from 150 – 500 l/min in 3 stages.

## Technical specifications

Output	2200 W	Replaceable heating element	No
Temperature	80 – 630 °C	Restart protection	No
Airflow rate	150 – 500 l/min	Thermal cut-out	Yes
Motor, type	Brush motor	Cord length	2.2 m
Temperature setting	Continuous	Dimensions (L x W x H)	253 x 87 x 200 mm
Temperature display	Thumbwheel with labelled settings	Mains power supply	220 – 230 V / 50 – 60 Hz
Heating element	Ceramic heating element	PU1, net weight	1,191 kg
Loc function	No	Manufacturer's Warranty	1 year
Residual heat indicator	No	PU1, EAN	4007841008024
Function, hanger	Yes		

## Accessories

EAN 4007841 071219	HDPE plastic welding rod
EAN 4007841 073411	PP plastic welding rod
EAN 4007841 073114	PVC plastic welding rod
EAN 4007841 074210	ABS plastic welding rod
EAN 4007841 009601	Flexible hot air tool stand with suction pad foot
EAN 4007841 014919	Temperature scanner HL Scan
EAN 4007841 009595	Flexible hot air tool stand with magnetic foot
EAN 4007841 075569	12-piece hot-air accessory kit
EAN 4007841 053963	Hot Air Tool Guard Cage HL 1820 S - HG 2320 E