


Spot Garden

Sensor Connect

EAN 4007841 058685



LED

20.000 h

3000K
warm-white

38°

Infrared sensor
90°

max. 10 m



IP44



90° vertical

2 - 2000 lux (via
App)5 sec - 60 min (via
App)

manual override

Function description

Interconnected garden enjoyment. The Spot Garden Sensor Connect ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 520 lm, 7 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm	Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m ²)
Mains power supply	220 – 240 V / 50 – 60 Hz	Photo-cell controller	Yes
Sensor Technology	passive infrared	Twilight setting	2 – 2000 lx
Output	7 W	Time setting	5 s – 60 Min.
Interconnection	Yes	Basic light level function	No
Slave modeselectable	Yes	Functions	Digital timer, Master/slave override
Luminous flux	520 lm	Soft light start	No
Colour temperature	3000 K	Continuous light	selectable, 4h
Colour variation LED	SDCM5	Impact resistance	IK03
Colour Rendering Index CRI	80-89	IP-rating	IP44
With lamp	Yes, LED lamp	Protection class	II
Lamp	LED can be replaced	Ambient temperature	-20 – 40 °C
With motion detector	Yes	Housing material	Aluminium
Detection angle	90 °	Cover material	Plastic, transparent
Angle of aperture	90 °	Manufacturer's Warranty	3 years
Sneak-by guard	No	PU1, net weight	0,71 kg
Capability of masking out individual segments	No	Version	Sensor Connect
Reach, radial	passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m ²)	PU1, EAN	4007841058685

Floodlight


Spot Garden

Sensor Connect

EAN 4007841 058685



Detection Zone



Mögliche Montagehöhe: –
Orange: radial
Schwarz: tangential

Dimension Drawing

