

GluePRO 400 LCD

Folding box
 EAN 4007841 035297
 Article number 035297



<2 min.

Quickstart

40-230 °C

Degree-accurate temperature setting

1,5 kg/h

High adhesive performance

ø 11 mm

Klebesticks



CE



EMC

Function description

Professional gluing to the accuracy of a degree. Virtually any hot-melt adhesive can be used. Including acrylates demanding a high temperature or low-temperature Low Melt adhesives. The GluePRO 400 LCD is the ergonomic hot-melt glue applicator for professional use in industry and the trades, producing optimum results with the capability of setting the temperature to an accuracy of one degree. With a display for monitoring temperature to the accuracy of one degree (40-230°C). Heats up in under two minutes.

Technical specifications

Output	400 W
Temperature	40 – 230 °C
Warm-up time	2 min
Delivery rate	33 gr/min
Max. stick diameter	11.7 mm
Temperature display	LCD display
Function, hanger	Yes
Soft grip	Yes
Idle mode	Yes
Nozzle can be changed	Yes
Stroke adjustment	Yes
Temperature, adjustable	Yes
Temperature accuracy +/-	2 °C

Heating element	PTC heating element
Voltage range (min)	220 V
Restart protection	Yes
Melt temperature	40 – 230 °C
Cord length	max.
Dimensions (L x W x H)	230 x 70 x 290 mm
Version	Folding box
PU1, net weight	0,6 kg
Manufacturer's Warranty	1 year
PU1, EAN	4007841035297
Power plug	Typ F
Average power consumption	110 W

Accessories

EAN 4007841 052416

Acrylate glue sticks ø 11 mm

Hot-melt glue applicator - Professional Line

GluePRO 400 LCD

Folding box
EAN 4007841 035297
Article number 035297



Accessories

EAN 4007841 052430	Fast glue sticks Ø 11 mm
EAN 4007841 052423	Flex glue sticks Ø 11 mm
EAN 4007841 052409	Low Melt glue sticks Ø 11 mm
EAN 4007841 050092	General-purpose glue sticks Ø 11 mm
EAN 4007841 052737	Long nozzle
EAN 4007841 052928	Long nozzle, Ø 1.5 mm
EAN 4007841 052935	Long nozzle
EAN 4007841 052744	Long nozzle, angled, Ø 3.0 mm