

GluePRO 400 LCD

Case
EAN 4007841 052690



<2 min.

40-230 °C

1,5 kg/h

Ø11mm



Quickstart

Degree-accurate
temperature
setting

High adhesive
performance

Glue sticks

CE

EMC

Function description

Professional gluing to the accuracy of a degree. Virtually any hot-melt adhesive can be used. Including acrylates demanding a high temperature or low-temperature Low Melt adhesives. The GluePRO 400 LCD is the ergonomic hot-melt glue applicator for professional use in industry and the trades, producing optimum results with the capability of setting the temperature to an accuracy of one degree. With a display for monitoring temperature to the accuracy of one degree (40-230°C). Heats up in under two minutes.

Technical specifications

Output, heat-up phase	400 W
Average power consumption	110 W
Temperature	40 – 230 °C
Temperature display	LCD display
Melt temperature	40 – 230 °C
Temperature accuracy +/-	2 °C
Warm-up time	2 min
Delivery rate	30 gr/min
Max. stick diameter	11.7 mm
Function, hanger	Yes

Soft grip	Yes
Stroke adjustment	Yes
Idle mode	Yes
Dimensions (L x W x H)	230 x 70 x 290 mm
Nozzle can be changed	Yes
Mains power supply	220 – 230 V / 50 – 60 Hz
PU1, net weight	0,6 kg
Manufacturer's Warranty	1 year
PU1, EAN	4007841052690

GluePRO 400 LCD

Case

EAN 4007841 052690



Accessories

EAN 4007841 052737	Long nozzle, Ø 3.0 mm
EAN 4007841 052744	Long nozzle, angled, Ø 3.0 mm
EAN 4007841 052928	Long nozzle, Ø 1.5 mm
EAN 4007841 052935	Long nozzle, Ø 4.5 mm
EAN 4007841 052416	Acrylate glue sticks Ø 11 mm
EAN 4007841 052430	Fast glue sticks Ø 11 mm
EAN 4007841 052423	Flex glue sticks Ø 11 mm
EAN 4007841 052409	Low Melt glue sticks Ø 11 mm
EAN 4007841 050092	General-purpose glue sticks Ø 11 mm