


Spot Way

Sensor Connect

EAN 4007841 058661

Article number 058661



LED

20.000 h



3000K
warm-white



38°



infrared sensor
90°



max. 10 m



Twilight switch



IP44



180° horizontal,
90° vertical



2 - 1000 lux



5 sec - 60 min

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 520 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm	Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m ²)
Mains power supply	220 – 240 V / 50 – 60 Hz	Photo-cell controller	Yes
Mounting height max.	2,50 m	Twilight setting	2 – 2000 lx
Sensor Technology	passive infrared	Time setting	5 s – 60 Min.
Output	7 W	Basic light level function	No
Power consumption	0,5 W	Main light adjustable	No
Interconnection	Yes	Functions	Digital timer, Master/slave override
Slave modeselectable	Yes	Settings via	Bluetooth
Luminous flux	520 lm	Soft light start	No
Colour temperature	3000 K	Continuous light	selectable, 4h
Colour variation LED	SDCM5	Impact resistance	IK03
Colour Rendering Index CRI	80-89	IP-rating	IP44
With lamp	Yes, LED lamp	Protection class	II
Lamp	LED can be replaced	Ambient temperature	-20 – 40 °C
With motion detector	Yes	Housing material	Aluminium
Detection angle	90 °	Cover material	Plastic, transparent
Angle of aperture	90 °	Manufacturer's Warranty	3 years
Sneak-by guard	No	PU1, net weight	1,23 kg
Capability of masking out individual segments	No	Version	Sensor Connect
Reach, radial	passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m ²)	PU1, EAN	4007841058661

Sensor-switched LED floodlight

Spot Way


Sensor Connect

EAN 4007841 058661

Article number 058661



Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

Dimension Drawing

