

Presence detector - Professional Line

IR Quattro SLIM XS

V2 KNX - square

EAN 4007841 033033



infrared sensor
360°



max. 4 x 4 m
presence



IP20



KNX



10 - 1000 lux



ideal 2,5 - 4 m

TEACH

Teach mode

iQ

iQ-mode

5 JAHRE
HERSTELLER
GARANTIE

manufacturer's
warranty
[steinel-professional.de/garantie](https://www.steinel-professional.de/garantie)



CE

Function description

Noticeably Inconspicuous. IR Quattro SLIM XS KNX, the extra-slim presence detector in concealed-box format. Fits into any standard concealed box. Overall height of just 6 mm. High-precision 360° infrared sensor with globally unique retina lens and 16 sq.m square presence detection zone (4 x 4 m). Adjustment via remote control or Smart Remote.

IR Quattro SLIM XS

V2 KNX - square

EAN 4007841 033033



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	60 x 77 x 77 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, room	one-person office, hotel room, care room, function room / ancillary room, WC / washroom, Indoors
Installation site	ceiling
Installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	4 x 4 m (16 m ²)
Reach, tangential	4 x 4 m (16 m ²)
Reach, presence	4 x 4 m (16 m ²)
Twilight setting TEACH	Yes

Twilight setting	10 – 1000 lx
Time setting	60 s – 60 Min.
Basic light level function	Yes
Basic light level function in per cent	10 – 50 %
Basic light level function time	Permanently ON, 1-255 min, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
KNX functions	Light output 4x, Presence output, Light level, Constant-lighting control, Basic light level function, HVAC output
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
Interconnection	Yes
Type of interconnection	Master/slave, Master/master
IP-rating	IP20
Material	Plastic
Ambient temperature	0 – 40 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX - square
PU1, EAN	4007841033033

Accessories


EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

IR Quattro SLIM XS

V2 KNX - square

EAN 4007841 033033

Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m

Orange: Präsenz, tangential und radial

Dimension Drawing

