

# Dual US

V3 KNX - Concealed wiring  
 EAN 4007841 059491  
 Article number 059491



ultrasonic sensor  
360°



3 x 20 m



KNX 4 channel



IP20



ideal 2,5 - 3,5 m



indoor sensor



iQ-mode

Teach

Teach mode



energy saving

5 years

manufacturer's warranty steinel-professional.de/garantie

## Function description

Watches over the entire corridor. And can see around corners. Dual US KNX ultrasonic motion detector, ideal for corridors and passageways. Reliable detection within 20 m, envelops objects as opposed to penetrating them, detection regardless of temperature, electronically adjustable reach, with digital BUS interface for controlling 4 lighting channels and HVAC.

## Technical specifications

Dimensions (L x W x H)	70 x 120 x 120 mm	Mounting height max.	3,50 m
With motion detector	Yes	Optimum mounting height	2,8 m
Manufacturer's Warranty	5 years	Ultrasonic technology	40 kHz
Settings via	ETS software, Remote control, Bus, Smart Remote	Detection angle	Aisle, 360 °
With remote control	No	Angle of aperture	180 °
Version	KNX - Concealed wiring	Sneak-by guard	Yes
PU1, EAN	4007841059491	Capability of masking out individual segments	No
Type	Presence detector	Electronic scalability	Yes
Application, place	Indoors	Mechanical scalability	No
Application, room	corridor / aisle, Indoors	Reach, radial	20 x 3 m (60 m <sup>2</sup> )
Colour	white	Reach, tangential	20 x 3 m (60 m <sup>2</sup> )
Colour, RAL	9010	Twilight setting	10 – 1000 lx
Includes corner wall mount	No	Time setting	10 s – 1092 Min.
Installation site	ceiling	Basic light level function	Yes
Installation	Concealed wiring, Ceiling	Basic light level function time	1-255 min
IP-rating	IP20	Main light adjustable	0 - 100 %

# Dual US

V3 KNX - Concealed wiring  
 EAN 4007841 059491  
 Article number 059491



## Technical specifications


Ambient temperature	von -25 bis zu 55 °C
Material	Plastic
Mains power supply	30 V
Power consumption	0,7 W
Power supply, detail	KNX bus
With bus coupling	Yes
Technology, sensors	Photo-cell controller, Ultrasonic
Mounting height	2,50 – 3,5 m

Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	17,5 mA

## Accessories

EAN 4007841 002855	Clamping-type ceiling adapter Control PRO UP Box
EAN 4007841 000363	Surface-mounted adapter Control Pro IP54
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

## Detection Zone



Possible mounting height: 2,50 m – 3,50 m  
 Orange: radial and tangential

## Dimension Drawing

