

Light Sensor Dual

V3 KNX - concealed, sq.
EAN 4007841 058326



Twilight switch +
eco-mode



KNX



IP20



2 - 1000 lux



max 4 m



CE



5 JAHRE
HERSTELLER
GARANTIE
manufacturer's
warranty
steinel-professional.de/garantie

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

| | |
|----------------------------|--|
| Type | Constant-lighting controller |
| Dimensions (L x W x H) | 51 x 94 x 94 mm |
| Sensor Technology | Light sensor |
| Application, place | Outdoors, Indoors |
| Installation site | wall, ceiling |
| Installation | Concealed wiring |
| Mounting height | 2,00 – 4,00 m |
| Twilight setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Constant-lighting control | Yes |
| Basic light level function | Yes |
| KNX functions | Light output 2x, Light level, Constant-lighting control, Photo-cell controller, Logic gate |

| | |
|-------------------------|---|
| With bus coupling | Yes |
| Settings via | ETS software, Remote control, Bus, Smart Remote |
| Interconnection | Yes |
| Type of interconnection | Master/master, Master/slave |
| IP-rating | IP20 |
| Ambient temperature | -20 – 50 °C |
| Application, room | classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room, Indoors |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |
| Version | KNX - concealed, sq. |
| PU1, EAN | 4007841058326 |

Photo-cell controller - Professional Line

Light Sensor Dual

V3 KNX - concealed, sq.

EAN 4007841 058326



Dimension Drawing

