




# Recessed ceiling sensors

## The quickest solution for suspended ceilings.

Our adapters, developed specially for suspended ceilings, enable the quick and easy installing, mounting and commissioning of sensors. Currently, there are 13 STEINEL motion sensors and presence detectors with different interfaces available as a recessed ceiling version. The recessed ceiling adapter is also available as an accessory.



 professional line

<p>3</p> <p>Available for COM1, DALI-2 APC and KNX interfaces</p>	 <p>68mm</p> <p>Ideal for ceiling cut-outs with a 68-mm diameter</p>	<p>38</p> <p>38 recessed ceiling sensors for our 3000, Control PRO and Control PRO II series</p>	 <p>The recessed ceiling adapter is available as an accessory for retrofitting existing UP sensors in the 3000, Control PRO and Control PRO II series.</p>
-------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# Overview of recessed ceiling sensors

Product group	Product	Interface	Detection	EAN
<b>3000-series motion sensor</b> 	IS 3360 rectangular	COM1	Ø 40 m	4007841 079635
		DALI-2 APC	Ø 40 m	4007841 080624
		KNX V3.1	Ø 40 m	4007841 079642
	IS 3360 round	COM1	Ø 40 m	4007841 079659
		DALI-2 APC	Ø 40 m	4007841 080631
		KNX V3.1	Ø 40 m	4007841 079666
	IS 345 rectangular	COM1	24 x 3 m	4007841 079673
		DALI-2 APC	24 x 3 m	4007841 080648
		KNX V3.1	24 x 3 m	4007841 079680
	IS 345 round	COM1	24 x 3 m	4007841 079697
		DALI-2 APC	24 x 3 m	4007841 080655
		KNX V3.1	24 x 3 m	4007841 079703
<b>Control PRO presence detector</b> 	IR Quattro	COM1	max. 4 x 4 m presence	4007841 079345
		DALI-2 APC	max. 4 x 4 m presence	4007841 079352
		KNX V3.1	max. 4 x 4 m presence	4007841 079390
	IR Quattro HD	COM1	max. 8 x 8 m presence	4007841 079369
		DALI-2 APC	max. 8 x 8 m presence	4007841 079376
		KNX V3.1	max. 8 x 8 m presence	4007841 079383
	Dual HF	COM1	max. 20 x 3 m	4007841 079482
		DALI-2 APC	max. 20 x 3 m	4007841 079499
		KNX V3.1	max. 20 x 3 m	4007841 079505
	HF 360	COM1	max. Ø 12 m	4007841 079512
		DALI-2 APC	max. Ø 12 m	4007841 079529
		KNX V3.1	max. Ø 12 m	4007841 079536
	Dual US	COM1	max. 20 x 3 m	4007841 079598
		KNX V3.1	max. 20 x 3 m	4007841 079604
	US 360	COM1	max. Ø 10 m	4007841 079611
		KNX V3.1	max. Ø 10 m	4007841 079628
	Dual Tech	COM1	max. Ø 10 m	4007841 079574
		KNX V3.1	max. Ø 10 m	4007841 079581
<b>Control PRO II presence detector</b> 	IR Quattro HD-2	COM1	max. 9 x 9 m presence	4007841 079406*
		KNX V3.5	max. 9 x 9 m presence	4007841 079413*
	HF 360-2	COM1	max. Ø 12 m	4007841 079420
		KNX V3.5	max. Ø 12 m	4007841 079437
	True Presence®	COM1	max. Ø 15 m	4007841 079444
		KNX V3.0	max. Ø 15 m	4007841 079451
	Hallway	COM1	max. 25 x 3 m	4007841 079468
		KNX V3.5	max. 25 x 3 m	4007841 079475
<b>Accessories</b>	3000-series adapter, Control PRO and Control PRO II			4007841 079543

\* from Q4/2021