


HB PIR 3360 IPD




110088245 SENSOTEC Sensor HB PIR 3360 IPD Intra
 110088246 SENSOTEC Sensor HB PIR 3360 IPD Wire
 110088247 SENSOTEC Sensor HB PIR 3360 IPD Zhaga



A head for heights. Powerful reach. Reliable. Ideal for high ceilings in industrial buildings or commercial properties. For mounting heights of up to 14 m. High-precision 360° infrared sensor. Maximum detection range diameter 36 m. For watching over up to 1000 sqm.



Technical specifications

DALI instances	Occupancy sensor (type 3) / Light sensor (type 4)		
Sensor technology	Passive infrared technology		
3D data	available online		
Light measurement range	4 - 1000lx		
Mounting height	2.8 - 14.0 m		
Reach, radial	Ø 14 m (154 m ²)		
Reach, tangential	Ø 36 m (1018 m ²)		
Supply voltage / current consumption	12 - 22.5VDC / max. 16mA		
Temperature range	-20 to +50°C		
tc	50°C		
Interfaces	DALI		
Approval marks / Conformity	CE, DALI2		
Standards	EN 61347-1 / EN 61347-2-11 / EN 55015 / EN 61547 / EN 62386-101 / EN 62386-103 / EN 62386-303 / EN 62386-304		
Connection options	HB PIR 3360 IPD Intra	HB PIR 3360 IPD Wire	HB PIR 3360 IPD Zhaga
			
GTIN	4007841085414	4007841085421	4007841085438
Type	9016	9022	9021
Dimensions	91.5 × 63.3 × 49 mm	91.5 × 63.3 × 49 mm	91.5 × 63.3 × 57 mm
Connection	0.34 – 0.75mm ²	Connection strands (0.5mm ² , L=250mm, weiss)	Zhaga Book 18
IP rating	IP20 / IP65 (sealed lense)	IP65	IP65

Downloads

[Data sheet SENSOTEC IPD](#)

[EU Declaration of Conformity](#)

[3D data](#)