





HB PIR 3360 NET

110075223 SENSOTEC Sensor HB PIR 3360 NET Intra
 110075224 SENSOTEC Sensor HB PIR 3360 NET Wire
 110075225 SENSOTEC Sensor HB PIR 3360 NET Zhaga

A head for heights. Powerful reach. Reliable. Ideal for high ceilings in industrial buildings or commercial properties. For mounting heights of up to 14 m. High-precision 360° infrared sensor. Maximum detection range diameter 36 m. For watching over up to 1000 sqm.



Technical specifications

Features	Motion detector, light sensor, feedback indicator, Bluetooth mesh		
Sensor technology	Passive infrared technology		
Configuration	via app		
3D data	available online		
Light measurement range	4 - 1000lx		
Mounting height	2.8 – 14.0 m		
Reach, radial	Ø 14 m (154 m ²)		
Reach, tangential	Ø 36 m (1018 m ²)		
Supply voltage / current consumption	12 - 22.5VDC / max. 46mA		
Temperature range	-20 to +50°C		
tc	50°C		
Bluetooth Range	35 m		
Interfaces	DALI, Bluetooth		
Approval marks / Conformity	CE		
Standards	EN 61347-1 / EN 61347-2-11 / EN 55015 / EN 61547 / EN 301 489-1		
Connection options	HB PIR 3360 NET Intra	HB PIR 3360 NET Wire	HB PIR 3360 NET Zhaga
			
Bluetooth Device Name	STE HB PIR 3360 NET I	STE HB PIR 3360 NET W	STE HB PIR 3360 NET Z
Type	9016	9022	9021
Dimensions	91.5 × 63.3 × 49 mm	91.5 × 63.3 × 49 mm	91.5 × 63.3 × 57 mm
Connection	0.34 – 0.75mm ²	Connection strands (0.5mm ² , L=250mm, white)	Zhaga Book 18
IP rating	IP20 / IP65 (sealed lens)	IP65	IP65

Downloads

[Data sheet SENSOTEC NET](#)

[EU Declaration of Conformity](#)

[3D data](#)