


110088253

SENSOTEC Sensor PIR IPD

Small. Slim. Compact. Inconspicuous presence detectors. 360° passive infrared sensor with a presence detection zone of 4 x 4 m (presence and radial movement detection) or 6 x 6 m (tangential movement detection). With fresnel lens.



Technical specifications

GTIN	4007841085483
Type	9026
Dimensions	66.4 × 20.4 × 18.5 mm Fixing spacing 35 mm
3D data	available online
DALI instances	Occupancy sensor (type 3) / Light sensor (type 4)
Sensor technology	Passive infrared technology
Transmitter power	-
Transmission frequency	-
Light measurement range	4 - 1000lx
Angle of coverage	-
Mounting height	2.0 – 5.0 m
Optimum mounting height	2.8 m
Reach, radial	4 x 4m (16 m ²)
Reach, tangential	6 x 6m (36 m ²)
Connection	0.34 – 0.75mm ²
Supply voltage / current consumption	12 - 22.5VDC / max. 16mA
IP rating	IP20
Temperature range	-25 to +55°C
tc	55°C
Interfaces	DALI
Approval marks / Conformity	CE / DALI-2
Standards	EN 61347-1 / EN 61347-2-11 / EN 55015 / EN 61547 / EN 62386-101 / EN 62386-103 / EN 62386-303 / EN 62386-304

Downloads

[Data sheet SENSOTEC IPD](#)
[EU Declaration of Conformity](#)
[3D data](#)